



**SLOVENSKA
AKREDITACIJA**
SIST EN ISO/IEC 17065
CP-002

ZAG

**ZAVOD ZA
GRADBENIŠTVO
SLOVENIJE**

SLOVENIAN
NATIONAL BUILDING
AND CIVIL ENGINEERING
INSTITUTE

Dimičeva ulica 12
1000 Ljubljana
Slovenija

info@zag.si
www.zag.si

Notified certification body
NB 1404

Certificate of constancy of performance

1404 – CPR – 3380

(English translation, the original version is in Slovenian)

In compliance with Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction products Regulation or CPR), this certificate applies to the construction products

self supporting double skin metal faced insulating panels

placed on the market under the name or trade mark of

**TRIMO d.o.o.,
Prijateljeva cesta 12, 8210 Trebnje, Slovenia**

and produced in the manufacturing plants

Plant 1 and Plant 2.

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard

EN 14509:2013

under system 1 for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the

constancy of performance of the construction products.

This certificate was first issued on **26. 10. 2021** and will remain valid until **26. 10. 2026** as long as neither the harmonised standard, the construction products, the AVCP method nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

Detailed information about the scope of the products is given in the annex to this certificate.

Ljubljana, 26. 10. 2021

Authorised signatory of the Certification body:

Vesna Krajnc Brodar, B. Sc.



Scope of the certificate:

A) Plant 1 and Plant 2: Products for use on roofs, roof coverings, walls, wall coverings and ceilings

Product type	Joint design	Reaction to fire	Type and thickness of metal facing	Type of insulating core
Trimoterm Perform R	FTV 50 to FTV 250, SNV 60 to SNV 200 and 240	A2 – s1, d0	Thickness of galvanized metal facing 0,3 to 1,2 mm	MW from 100 kg/m ³ to 120 kg/m ³
Trimoterm Perform C	FTV 50 to FTV 250, FTV HL 50 to FTV HL 250,			MW 120 kg/m ³
Trimoterm Power T	SNV 60 to SNV 200 and 240			MW 90 kg/m ³
Trimoterm Power S	FTV 50 to FTV 250, FTV HL 50 to FTV HL 250	A2 – s1, d0	Thickness of galvanized metal facing 0,3 to 1,2 mm	MW 120 kg/m ³
Trimoterm Power B				

B) Plant 1: Products for use on walls, wall coverings and ceilings

Product type	Joint design	Reaction to fire	Type and thickness of sheet metal	Type of insulating core
Qbiss One C	B-B, B-BF, BF-B, BF-BF, F-B, F-BF, BX; 80 to 250	A2 – s1, d0	Thickness of galvanized metal facing 0,3 to 1,2 mm	MW 120 kg/m ³
Qbiss One S				MW 120 kg/m ³
Qbiss One T				MW 90 kg/m ³
Qbiss Screen MW	B-B, B-BF, BF-B, BF-BF, F-B, F-BF; 65 mm			MW 120 kg/m ³

End of the Annex

