


TRI MO TRIMOTERM



TRIMOTERM FTV
FAÇADE INSTALLATION GUIDE

For general contractors and installation team!

Installation guide for Trimoterm FTV panels.



Descriptions of details, and other information in this document, are only provided to illustrate the system(s) of Trimoterm cladding products and applications. Each user of such information is fully responsible for the incorporation of this advisory information in their designs.

Trimo assumes no liability whatsoever for any damages incurred by you resulting from errors in or omissions from the information included herein.

Care has been taken to ensure that information contained in this document is accurate, but Trimoterm, including its subsidiaries, does not accept responsibility or liability for errors in information.

Table of contents

A	General	04
A1	Guidelines	
A1.1	Introduction	
A1.2	Safety regulations	
A1.3	Owner's / Contractor's responsibilities	
A2	Package description	
A2.1	Size and weight of the package	
A2.2	Specification of packages	
A2.3	Panel description	
A2.4	Panel tolerances	
A2.5	Panel identification	
A2.6	Receiving	
A3	Package unloading	
A4	Temporary storage on site	
A5	Handling during installation	
A5.1	Manual lifting	
A5.2	Lifting with vacuum lifters	
A5.3	Lifting with mechanical grippers	
A6	Installation tools	
A6.1	Tools and gear for installation	
A6.2	Panel cutting	
A6.3	Sealing the facade	
B	Installation guide	20
B1	General warnings for installers	
B1.1	Installation direction	
B2	Fastening scheme on the panel edge	
B3	Installation preferences	
B3.1	Installation and control of structure	
B3.2	Thermal bow	
B3.3	Protective foil removal	
C	Installation sequences	26
C1	Horizontal orientation	
C1.1	Preparation for panel installation	
C1.2	Installation of the first row of panels	
C1.3	Installation of the remaining panels	
C1.4	Finalising panel wall with flashings	
C2	Vertical orientation	
C2.1	Preparation for panel installation	
C2.2	Installation of the first row of panels	
C2.3	Installation of the remaining panels	
C2.4	Finalising panel wall with flashings	
C3	Trimoterm FTV installation check list	
D	Installation details	44
D1	Horizontal installation details	
D1.1	Panel joint (fasteners and sealants)	
D1.2	Panel base	
D1.3	Parapet wall	
D1.4	External corner	
D1.5	Internal corner	
D1.7	Panel penetration (field of panel example)	
D2	Vertical installation details	
D2.1	Panel joint (fasteners and sealants)	
D2.2	Panel base	
D2.3	Parapet wall	
D2.4	External corner	
D2.5	Internal corner	
D2.7	Panel penetration (field of panel example)	
D3	Flashing and profile guidelines	
D3.1	Flashing mask extension and fitting	
D3.2	Drip flashing extension and fitting	
D3.3	Parapet cap extension and fitting	
D3.4	Fitting of aluminium HF102 fixing profile	
D3.5	Fitting of aluminium HF140 extension profile	
E	Life-cycle management	64
E1	Replacement of damaged panels	
E1.1	Replacement principles	
E2	Panel life-cycle assessment	
E3	End of panel life-cycle	
F	Trimoterm documents	67
F1	Related Trimoterm documents	

A

General

A1 Guidelines

A1.1 Introduction

This installation guide provides step-by-step instructions for installing both horizontal and vertical series of all Trimoterm FTV wall panels.

A1.2 Safety regulations

All safety procedures, including but not limited to fall protection and material handling, are the exclusive responsibility of the installing contractor.

To prevent accidents and health hazards, always follow safety protocols. Before installation work, check whether the installation site is subject to any particular requirements regarding occupational safety. Always follow local occupational safety provisions.

A1.3 Owner's / Contractor's responsibilities

- A qualified and experienced installer, with demonstrated expertise in the proper installation of insulated metal panels and associated construction elements, must be selected.
- The installer must review and fully understand both the project's installation drawings and this installation guide prior to beginning work.
- All panels and related components must be installed in strict accordance with the project's installation drawings and with the relevant sections of this guide.
- Panels must be verified as suitable for their intended application.
- The project's structural framing must be properly designed and in suitable condition to support the erection and the design loads imposed by the wall panels.
- The placement of interior and/or exterior panel joints and perimeter seals must be correctly specified in accordance with the project's moisture and vapor control requirements.
- Installation must comply with all applicable codes, regulations, service conditions, and recognized standards of good engineering and construction practice.

A Package

A2 Package description

Trimoterm FTV packaging protects panels during transport, handling and storage. Clear labelling and correct stacking improve safety and logistics efficiency. The packaging fit the entire Trimoterm FTV range regardless of type or thickness and is designed to minimise environmental impact at the end of their lifecycle.

A2.1 Size and weight of the package

Max. width (A)	Max. length (L)	Standard height (H)	Max. weight
1,230 mm	13,000 mm (13,200 mm)*	1,000 - 1,320 mm	3,000 kg

* Value for standard transport; Non-standard transport 13,200 mm - 14,200 mm.

Tab. 1.1: Package maximal dimension and weight.

A2.2 Specification of packages

This specification lists all packages and their key data (number, size, weight, packing type, contents). Use it to verify deliveries on site.

STAT. CODE	PACKET NO.	DESCRIPTION	PACKAGE LENGTH	PACKAGE WIDTH	PACKAGE HEIGHT	PACKAGE WEIGHT	GROSS WEIGHT				NET WEIGHT	
							QUANTITY	UNIT	PACKING TYPE	UNIT Q. UM	WEIGHT LENGTH	UM
ODPR 0000117911-00001		6.300	1.000	920 MM	1174,4	1159,4	1174,4	KG	STYRO-FOAM/CARDBOA	10 PC	6.200 MM	SURESTE DE 01 A 04 + MERMA
81031666 Trimoterm Power S FTV HL-80/1000				62,000 M2								
MS 0,60 mm PVDF 35 µm R9007 / 0,50 mm SP 25 µm R9002												
ODPR 0000117911-00002		6.300	1.000	920 MM	1174,4	1159,4	1174,4	KG	STYRO-FOAM/CARDBOA	10 PC	6.200 MM	SURESTE DE 01 A 04 + MERMA
81031666 Trimoterm Power S FTV HL-80/1000				62,000 M2								
MS 0,60 mm PVDF 35 µm R9007 / 0,50 mm SP 25 µm R9002												
ODPR 0000117911-00003		6.300	1.000	920 MM	1174,4	1159,4	1174,4	KG	STYRO-FOAM/CARDBOA	10 PC	6.200 MM	SURESTE DE 01 A 04 + MERMA
81031666 Trimoterm Power S FTV HL-80/1000				62,000 M2								
MS 0,60 mm PVDF 35 µm R9007 / 0,50 mm SP 25 µm R9002												

Fig. 1.0


More information about package elements is available in the following document:



Packaging, transport, and storage for Trimo products

A

Fig. 1.1: Trimoterm FTV panel package example (image is illustrative).



A2.3 Panel description

Panel thickness	50	60	80	100	120	133	150	172	200	220	240	250
Weight (Fe 0.55/0.5) [kg/m²]	15.8	17.0	19.4	21.8	24.2	25.8	27.8	30.5	33.8	29.7	38.6	32.4

Tab. 1.2: Weight of the panel (informative)




Fig. 1.2: Typical cross-section of a Trimoterm panel

A2.4 Panel tolerances

Tolerance is the acceptable upper and lower limit for measurements. It can be applied to every measurable aspect of a manufacturing element. The tolerances for rectangular Trimoterm FTV panels are in accordance with EN14509 standard.



Name	Dimension	Tolerance	Value [mm]	Remarks
Panel thickness	T	TS	$T \leq 100 \text{ mm} \dots \pm 2\text{mm}$ $T > 100 \text{ mm} \dots \pm 2\%$	Tolerance of element thickness
Panel length < 3 m	L	T1	$L \leq 3 \text{ m} \dots \pm 5 \text{ mm}$ $L > 3 \text{ m} \dots \pm 10 \text{ mm}$	Tolerance of external steel sheet length
Panel width	M	T2	± 2	Tolerance of the external steel sheet module width
Panel flatness [longitudinal]			0.6 mm 1.0 mm 1.5 mm	Flatness deviation of the external steel sheet surface in the longitudinal direction. Measurement length: $L = 200 \text{ mm}$ $L = 400 \text{ mm}$ $L = 700 \text{ mm}$
Panel end shift [transversal]	T7	± 2		Deviation of internal / external steel sheet position

Tab. 1.3



A

A2.5 Panel identification

Each panel in the package has its own identification number and a designated position on the facade, which must correspond to the project documentation. The data is printed on the internal side of the panel's longitudinal joint.

Using the delivery note and project documentation, you can accurately determine the installation position of each individual panel.

- 1. Panel position
- 2. Packet number




Fig. 1.3: Delivery note / statement of acquirer




Fig. 1.4: Individual panel installation reference (indicated on panel joint)

NOTES & WARNINGS

Panels of the same colour may differ slightly in shade, so it is important to install each panel in its assigned position as indicated on the panel and defined in the project layout. This ensures a consistent visual appearance for the facade.

A

A2.6 Receiving

Inspect goods delivered for any possible damage before unloading.

- Record any visible damage on the delivery note.
- Take a photo of the damaged goods immediately, while the goods are still on the truck.

Verify that the following details on the specification match the actual delivery:

- Order number
- Quantities
- Identity of all packages and panels

List of documents issued with each material dispatch:

1. Specification of packages

The document is typically sent with the order confirmation and includes a list of all packages to be manufactured and delivered.

2. Delivery note / statement of acquirer

The delivery note is issued after the material has been dispatched from the factory. It includes details about the delivery location and time, as well as a list of contents. Shortly before arrival, the truck driver contacts the designated contact person listed on the delivery note.

3. Instructions for acceptance, unloading, and storage, along with handling and installation instructions

A printed copy of the instructions is attached to the panel package. It contains important instructions regarding the unloading and storage of the packages.

4. Instructions for damage complaints

It contains detailed instructions on how to proceed in case the packages have been damaged during transport.

List of documents available on the Trimo website or provided upon special request:

1. Trimoterm FTV installation guide

The installation guide provides key instructions for installing Trimo panels. It is primarily intended for the installation team in order to ensure safety, efficiency, and correct handling during setup.

2. Packaging, transport and storage of Trimo products

A document that provides a detailed description of possible methods for packaging, transport, and storage of Trimo panels.



INTERNAL NUMBER
PROJECT 117911
CONSIGNEE TRIMOTERM FTV
ORDER NUMBER Matou
BUILDING SITE
ISSUED BY
DATE 28.08.2025

STAN. / PACKET NO.	PACKAGE	LENGTH	WIDTH	HEIGHT	PACKING TYPE	QUANTITY	NET / GROSS	NET / UM	LENTH / UM	POSITION
00000000000000000000	000	300	200	100	STANDARD	37	36	40		
00000000000000000001	000	300	200	100	STANDARD	1000	920.000	920.000	300.000	40
00000000000000000002	000	300	200	100	STANDARD	1000	920.000	920.000	300.000	40
00000000000000000003	000	300	200	100	STANDARD	1000	920.000	920.000	300.000	40
00000000000000000004	000	300	200	100	STANDARD	1000	920.000	920.000	300.000	40
00000000000000000005	000	300	200	100	STANDARD	1000	920.000	920.000	300.000	40
00000000000000000006	000	300	200	100	STANDARD	1000	920.000	920.000	300.000	40
00000000000000000007	000	300	200	100	STANDARD	1000	920.000	920.000	300.000	40
00000000000000000008	000	300	200	100	STANDARD	1000	920.000	920.000	300.000	40
00000000000000000009	000	300	200	100	STANDARD	1000	920.000	920.000	300.000	40
00000000000000000010	000	300	200	100	STANDARD	1000	920.000	920.000	300.000	40
00000000000000000011	000	300	200	100	STANDARD	1000	920.000	920.000	300.000	40
00000000000000000012	000	300	200	100	STANDARD	1000	920.000	920.000	300.000	40
00000000000000000013	000	300	200	100	STANDARD	1000	920.000	920.000	300.000	40
00000000000000000014	000	300	200	100	STANDARD	1000	920.000	920.000	300.000	40
00000000000000000015	000	300	200	100	STANDARD	1000	920.000	920.000	300.000	40
00000000000000000016	000	300	200	100	STANDARD	1000	920.000	920.000	300.000	40
00000000000000000017	000	300	200	100	STANDARD	1000	920.000	920.000	300.000	40
00000000000000000018	000	300	200	100	STANDARD	1000	920.000	920.000	300.000	40
00000000000000000019	000	300	200	100	STANDARD	1000	920.000	920.000	300.000	40
00000000000000000020	000	300	200	100	STANDARD	1000	920.000	920.000	300.000	40
00000000000000000021	000	300	200	100	STANDARD	1000	920.000	920.000	300.000	40
00000000000000000022	000	300	200	100	STANDARD	1000	920.000	920.000	300.000	40
00000000000000000023	000	300	200	100	STANDARD	1000	920.000	920.000	300.000	40
00000000000000000024	000	300	200	100	STANDARD	1000	920.000	920.000	300.000	40
00000000000000000025	000	300	200	100	STANDARD	1000	920.000	920.000	300.000	40
00000000000000000026	000	300	200	100	STANDARD	1000	920.000	920.000	300.000	40
00000000000000000027	000	300	200	100	STANDARD	1000	920.000	920.000	300.000	40
00000000000000000028	000	300	200	100	STANDARD	1000	920.000	920.000	300.000	40
00000000000000000029	000	300	200	100	STANDARD	1000	920.000	920.000	300.000	40
00000000000000000030	000	300	200	100	STANDARD	1000	920.000	920.000	300.000	40
00000000000000000031	000	300	200	100	STANDARD	1000	920.000	920.000	300.000	40
00000000000000000032	000	300	200	100	STANDARD	1000	920.000	920.000	300.000	40
00000000000000000033	000	300	200	100	STANDARD	1000	920.000	920.000	300.000	40
00000000000000000034	000	300	200	100	STANDARD	1000	920.000	920.000	300.000	40
00000000000000000035	000	300	200	100	STANDARD	1000	920.000	920.000	300.000	40
00000000000000000036	000	300	200	100	STANDARD	1000	920.000	920.000	300.000	40
00000000000000000037	000	300	200	100	STANDARD	1000	920.000	920.000	300.000	40
00000000000000000038	000	300	200	100	STANDARD	1000	920.000	920.000	300.000	40
00000000000000000039	000	300	200	100	STANDARD	1000	920.000	920.000	300.000	40
00000000000000000040	000	300	200	100	STANDARD	1000	920.000	920.000	300.000	40
00000000000000000041	000	300	200	100	STANDARD	1000	920.000	920.000	300.000	40
00000000000000000042	000	300	200	100	STANDARD	1000	920.000	920.000	300.000	40
00000000000000000043	000	300	200	100	STANDARD	1000	920.000	920.000	300.000	40
00000000000000000044	000	300	200	100	STANDARD	1000	920.000			

A

Unloading

A3 Package unloading

Follow the document 'Packaging, transport and storage for Trimo products' during package unloading. A link to the document is provided below.



Packaging, transport, and storage for Trimo products



PACKAGING, TRANSPORT AND STORAGE FOR
TRIMO PRODUCTS

Unloading can be carried out using:

- **Forklift (for packages shorter than 8 metres),**
- **Crane**

Ensure a level and sufficiently large surface for handling during unloading, depending on the situation. The unloading methods permitted also depend on the size and weight of the package – for details, refer to the document referred to above.




Fig. 1.7: Unloading panels from the side of flatbed trailer.




Fig. 1.8: Unloading package with crane.




Fig. 1.9: Lifting package using four-point harness.

A

Storage

A4 Temporary storage on site

Follow the document 'Packaging, transport and storage for Trimo products' strictly when storing the package.

Basic limitations

- The packaging is suitable for storing the package for up to 3 months.
- In case of deviations of storage condition, no warranty can be given.

Requirements

- Store panels on a fortified surface that prevents water accumulation (inclined terrain with ensured drainage).
- Store panels (packages) at least 100 mm above ground level using wooden planks or other durable material.
- Cover packages with a tarpaulin down to the bottom edge. Use a non-transparent cover with a minimum weight of 400 g/m².
- Ensure the bottom edge of the cover extends at least 50 mm below the package edge. Secure the cover mechanically.
- Ensure that the packages are drained and dry before covering fully.

Front side




Fig. 2.0: Trimoterm FTV panel package on site (tarpaulin covered).

A

Panel handling

A5 Handling during installation

Handle panels properly to prevent damage. Never slide or drag panels. Never place panels on their edge or on sharp/uneven surfaces.

There are three possible methods for lifting panels:

- Manual lifting
- Lifting with vacuum lifters
- Lifting with mechanical grippers





Fig. 2.1: Taking panels from the package properly.




Fig. 2.2: Do not slide panels across rough surfaces.




Fig. 2.3: Do not slide panels off package (scratches).

NOTES & WARNINGS

Panels must be protected from liquids seeping into insulation during unloading right through to the completion of installation.

It is contractor's responsibility to ensure the panels are protected until the completion of installation.

A

A5.1 Manual lifting

Panels that meet the manual handling weight limit may be lifted by two people.

Always transport panels upright, on their edge, and use EPS support blocks to protect the edges from damage.




Fig. 2.4: Permitted lifting points on the panels.

A5.2 Lifting with vacuum lifters

For lifting and positioning Trimoterm FTV panels at installation locations (for both vertical and horizontal facade installation), the use of a certified crane with vacuum grippers for sandwich panels is recommended. Panel installation time is typically reduced when using vacuum lifting equipment.

Use a certified crane with vacuum grippers for panel installation. Remove the protective foil from the areas where the panel will be gripped. Maximum vacuum suction pressure is 30 kPa.

When using vacuum grippers, follow the equipment manufacturer's instructions.



Packaging, transport, and storage for Trimo products



PACKAGING, TRANSPORT AND STORAGE FOR TRIMO PRODUCTS



Fig. 2.5: Setting horizontal panels with vacuum.

A

A5.3 Lifting with mechanical grippers

Use a special mechanical gripper for vertical or horizontal panel installation. Determine the gripper and pin dimensions statically, based on panel thickness and weight.

For horizontal facade installation, place the grippers in the longitudinal joint of the Trimoterm FTV mineral wool sandwich panel. Use two grippers per lift, except for small panels.

For vertical facade installation, use the gripper for panel lengths up to 14 metres. Before attaching the gripper to the panel's cut edge, place polystyrene foam underneath the panel and shift the panel by 200 mm to allow drilling. Attach the gripper so that the gravity axis of the panel passes through the gripper fastener.

If you need specific instructions on how to use mechanical grippers, please contact Trimo technical support.



Instructions for use - gripper for FTV panels

**TRI
MO**
TRIMOTERM

**TRI
MO**
TRIMOTERM



INSTRUCTIONS FOR USE / GRIPPER FOR HORIZONTAL FTV PANELS

INSTRUCTIONS FOR USE / GRIPPER FOR VERTICAL FTV PANELS




Fig. 2.6: Correct lifting with grippers for horizontal facade panels.




Fig. 2.7: Correct lifting with grippers for vertical facade panels.

A
Tools**A6 Installation tools****A6.1 Tools and gear for installation****Protective Gear**

Always follow safety protocols to prevent accidents and health hazards. Wear protective gloves and clothing when handling sharp elements, edges, and corners. Before starting installation work, check whether the site is subject to any specific occupational safety requirements. Always comply with local occupational safety regulations.

Measuring Tools

- Leveling laser
- Spirit level
- Plumb bob
- Measuring tape

Cutting and Forming Steel Sheets

- Metal shear
- Circular saw
- Jigsaw
- knife for insulation
- Tin snips (left, right) for cutting flashings
- Seaming tool

Drilling, Fastening, and Sealing Panels

- Cordless drill driver
- Rivet gun
- Drill bits
- Nut driver bit (typically SW8, for tightening screws)
- Caulking gun

A

A6.2 Panel cutting


Cutting and trimming of Trimoterm FTV panels, such as window and door openings or slanted cuts, is performed on-site by the installation company. Use only metal shears, fine-tooth saws, or metal circular saws that do not overheat the material at the cutting location. Do not use grinding machines or welding equipment near Trimoterm FTV sandwich panels.

Remove all metal swarfs from panel surfaces by the end of the working day to prevent corrosion caused by moisture exposure.


Recommended penetration positions

The recommendations below apply to small penetrations (up to 200 mm) that do not require reinforcement; however, the project designer must confirm whether reinforcement is needed in each specific case.


1. More than 100 mm from the panel edge.



2. Aligned with the panel edge (modules > 1000 mm).



3. Central to the joint (2/3 of panel width must be intact).



4. Between penetrations min. 300 mm




Fig. 2.8: Panel cutting tools

A

Basic cutting sequences

- Step 1: Be sure to allow adequate space for laying out and cutting panels.
- Step 2: Place the panel on padded sawhorses with the internal side up.
- Step 3: Mark the cut line with washable felt tip marker.
- Step 4: Apply masking tape to both sides of the cut line (required, if protective foil is not applied).
- Step 5: Cut the external steel sheet to a depth of 1 cm (use panel cutting tool).
- Step 6: Turn the panel over and cut the internal steel sheet to a depth of 1 cm (use panel cutting tool).
- Step 7: After both sheets are cut, cut the panel core using an insulation knife.
- Step 8: Gently sweep away metal swarf immediately after cutting.




Fig. 2.9: Panel cutting step 5



Fig. 3.0: Panel cutting step 7


B

Installation guide

B1 General warnings for installers before panel installation

1. Panel orientation

Do not rotate panels by 180°, as this may cause visible color differences at the joints. Install panels in the marked sequence and orientation.




2. Be aware of possible colour shade variations

Panels of the same colour may differ slightly in shade, so it is important to install each panel in its assigned position. Additionally, regularly check colour consistency from a distance of at least 25 metres and from multiple angles. Perform these checks before completing the installation of large surfaces to avoid extensive disassembly and replacement.


3. Supply of replacement panels

Verify panel quantities in advance and order reserves accordingly, as ordering and delivery of replacement panels may take time. Avoid construction delays by carefully checking and planning for stock availability.



4. Fastening elements

Before installation, verify that the type, quality, and quantity of fastening elements match the project design documentation and statical calculation. Use fastening elements made of stainless steel grade A2 or A4. Follow the recommended pre-drilling sizes and installation guidelines provided by the supplier.



5. Welding and grinding

Do not weld or use grinding tools near panels, as this may permanently damage the panel coating. Metal swarf should be gently sweep away immediately after cutting.



6. Weather conditions during installation

Install panels only in dry weather conditions, without precipitation or high humidity. Moisture during installation may cause water retention in joints, increasing the risk of corrosion and sealant failure. Strong winds can compromise the safe handling of panels, so in the event of strong winds, apply additional safety measures or postpone installation. Always check the local weather forecast before starting work, and prepare accordingly.



7. Surface Protection During Construction

Appropriate care must be taken to prevent scratches and mechanical damage to the panel surface. It is recommended that panels are protected when construction work is carried out close to them. Avoid the use of adhesive tapes, as certain types may adhere strongly to the surface and leave glue residue. If tape application is necessary, always test it on a concealed area beforehand and remove it promptly after use.

B

B1.1 Installation direction

The panels can be installed in both left-to-right and right-to-left directions, providing versatility in planning and execution. Always install panels from bottom to top. Installing elements from top to bottom is not permitted, as it may compromise the integrity and performance of the system.

HORIZONTAL PANEL ORIENTATION

1. column installation

Installation direction: LEFT>RIGHT or RIGHT>LEFT



Fig. 3.1

VERTICAL PANEL ORIENTATION

1. row installation

Installation direction: LEFT>RIGHT or RIGHT>LEFT





Fig. 3.2

B

Fastening scheme

B2 Fastening scheme on the panel edge

A fastening scheme for Trimoterm FTV panel edges (widths 1,000 mm and 1,200 mm) is shown below. Use a minimum of 2 fasteners per panel end. Position fasteners at least 25 mm from the transverse panel edges. Fasten panels to the sub-structure using through fasteners.



B

Preferences

B3 Installation preferences

B3.1 Installation and control of structure

Before panel installation, check the actual condition of the building and verify it against the panel layout in the execution drawings. The prescribed tolerances of the load-bearing structure must be observed (IFBS guideline PA 09 - Performance tolerance in light metal structures point 3.1.1).

Set-out gridlines and mark them on the building. Consider the actual element tolerances of the panels. Install each panel according to the gridlines set and consider/monitor installation and panel tolerances. Correct any deviations using appropriate measures during panel installation.

1. support structure alignment

single-span system $\pm 2L / 1,000$ (L-column axis distance)
multi-span system $\pm L / 1,000$ (L-column axis distance)

2. support structure torsion

single-span system $\pm 1^\circ$ / column torsion
multi-span system $\pm 0.5^\circ$

3. axis span tolerance

column width <200: ± 10 mm / columns width >200: ± 20 mm

4. column inclination tolerances

$\pm 1^\circ$

5. column height difference tolerance

± 20 mm

6. column curvature tolerance

± 10.0 mm / 10 m




Fig. 3.3

B

B3.2 Thermal bow

Panels exposed to direct sunlight may exhibit thermal bow which can prevent proper engagement. This phenomenon is intensified in the case of sheets in dark colors.

To correct this, move the panels to a shaded area or flip them over to expose the cooler side to sunlight for approximately 15 minutes. The panel will flatten back to its original shape and be ready for installation.




Fig. 3.4: Thermal bow correction.

B

B3.3 Protective foil removal

Protective foil, when present on the panel, prevents minor damage during handling and transport.

- Interior side of the panel: Remove the foil before panel installation.
- Exterior side of the panel: Remove the foil at locations where access will no longer be possible after installation (e.g., screw points, longitudinal joints). Otherwise, remove the foil from all installed panels no later than the end of the working day.
- For long-term storage of uninstalled panels, the protective foil must be removed in advance. For detailed information, refer to the document below.



Packaging, transport, and storage for Trimo products. document

TRI
MO



Fig. 3.5

C

Installation sequences

• C1 HORIZONTAL ORIENTATION

C1.1 PREPARATION FOR PANEL INSTALLATION

WALL 1 (COVER FLASHING & CORNER FLASHINGS)

Verify substructure placement

Confirm that the supporting structure is present in all locations necessary for panel installation. This includes extensions, the bottom edge on the foundation beam, the top edge at the parapet, and around window openings.

Check structural flatness

Assess the flatness of the substructure according to the guidelines outlined in chapter B3.1. Any deviations may affect panel alignment and sealing.

Confirm structural width

Ensure the substructure is wide enough to support the panels securely. For details involving flashings, maintain a proper gap (usually 20 mm) between adjacent panels to accommodate finishing elements.

Mark theoretical axes


Draw theoretical axis lines on the substructure to compare the actual situation with the design plans. This step is essential for accurate alignment and positioning during installation.

Install initial L-profile (longitudinal)

Position the L-profile along the designated line to define the starting edge of the panel installation.

Apply sealing tape

To ensure proper sealing and thermal performance, seal all holes and gaps in the substructure and install sealing tape along the perimeter of the installation area.



C

WALL 2 (HF PROFILE & CORNER ELEMENTS)

Corner verification


At building corners, measure dimensions in both directions to ensure that corner elements can be installed accurately and without misalignment.

Spacing with HF profiles

When using HF profiles, maintain a 40 mm gap between adjacent panels to accommodate the profile system and ensure proper fit.

Screw position check

Review the planned screw locations carefully. In specific details, the screw may align directly with the axis of the substructure, potentially colliding with the flange of an HEA profile. If such a conflict is identified, notify the project designer and agree on a suitable resolution.



! NOTES & WARNINGS

Use Trimoterm FTV installation guide as a general reference. Details may differ from project to project. Always follow project-specific execution details.

Use sealant material that complies with project design requirements for thermal insulation, tightness, and fire resistance.

In the event of any uncertainties, contact Trimo technical support.

C

• C1 HORIZONTAL ORIENTATION

C1.2 INSTALLATION OF THE FIRST ROW OF PANELS

WALL 1 (COVER FLASHING & CORNER FLASHINGS)

Install U-profiles

Mount U-profiles at intervals of 1.0 m, maintaining a 9 mm distance from the substructure to ensure proper fit into the panel groove. Before installing the first panel, install the base drip flashing. The gap between the support U-profiles and the panel is filled with mineral wool (class A1, density $\geq 100 \text{ kg/m}^3$).

installation gridline
(theoretical axis lines)

Place the first panel

Use one of the approved lifting methods described in Chapter A5. Check if the tongue of the panel being installed is facing the direction of lay. Align the first panel precisely in its intended position.


Avoid handling the panels in heavy wind ($< 9 \text{ m/s}$). To avoid a colour mismatch, pay particular attention to the installation direction and sequence.

Check horizontal alignment

Before fastening, use a spirit level to verify that the panel is horizontally aligned.

Fasten the panel

To ensure structural integrity, secure the panel using screws, as specified in the static calculation.



1. Drip flashing
2. Self adhesive sealing tape
3. Panel support profile

Each panel has its own unique production number and a designated position that directly correlates with the elevation plan in the project documentation.

direction of lay

Level and fasten the panel using the required number of screws, as determined by the static calculation. The screw arrangement is shown in Chapter B2.


Before installing the screws, remove the protective foil at each screw location.

Position the panel according to installation axes and verify that the panel is horizontally aligned and in line with the adjacent panel before fastening.

To ensure joint vapour and water tightness, sealing across external and internal side of the panel tongue (male joint) must be made. Do this for every panel installed.

Cut or fully remove the internal steel sheet of the standard panel at the building corner (to the panel thickness) to eliminate thermal bridging.

The gap between the support U-profile and the panel is filled with mineral wool thermal insulation. Ensure that the drip flashing is positioned correctly before installation of the first panel.



NEXT STEP

C

WALL 2 (HF PROFILE & CORNER ELEMENTS)

Corner support verification

Inspect the support conditions of corner elements to ensure they are not suspended without adequate bottom support.

Vertical load fixing (HF102)


For the HF102 system, install short screws together with a steel plate on the internal side of the panel to transfer vertical loads into the substructure.

Oznaka paketa / Package	52535-00058
Kupac / Customer	TRIMO UK LTD.
Stevika naročila / Purchase order number	80/2012; CA2316
Dimenzije paketa (mm) / Package dimensions (mm)	3075x1000x840
Opomba / Note	483 / 453
Material / Material	FHL120 M-MS-GREYAL PUR0707/8010SP0607-K4
Sarža / Batch	0001245607
Dolžina / Length	2975 mm
Kos/Piece	1 CA2316 GATEHOUSE/GH
Pozicija / Position	3 CA2316 GATEHOUSE/GH
Datum proizvodnje / Production date	2122090



Fig. 3.6: Each panel is clearly marked with individual installation reference (example on the right). With Trimoterm FTV panels the reference is indicated on internal side of longitudinal panel joint.

4. Panel marking position
5. Mastic sealant
6. Self adhesive sealing tape



NEXT STEP

C

• C1 HORIZONTAL ORIENTATION

C1.3 INSTALLATION OF REMAINING PANELS

WALL 1 (COVER FLASHING & CORNER FLASHINGS)

Apply mastic seal

Before placing the next panel on top of the bottom panel, apply mastic sealant to ensure airtightness on the internal side of the panel.

Compress panels to seal groove/tongue joint

Firmly compress the panels to ensure a tight joint connection. The weight of the upper panel assists in compressing the joint and supports proper sealing.

Check vertical alignment of panels

Always verify the vertical alignment of panels during installation. Horizontal and vertical lines must be properly aligned, with special attention to transitions to and connections with adjacent facade sections.

Remove protective foil from installed panels


Remove the protective foil from all installed panels no later than the end of the working day.

Fasten the panel

To ensure structural integrity, secure the panel using screws, as specified in the static calculation.

Protect panels against water and moisture

The installer is responsible for keeping panels dry until installation is complete. Trapped moisture can cause internal corrosion. Avoid installation during rain, snow, or dense fog.



C

WALL 2 (HF PROFILE & CORNER ELEMENTS)


Insert profile drip flashing at the bottom of the joint (for HF profiles)

Install the profile drip flashing into the 40 mm expansion gap between sandwich panels—either in the base/drip detail or at the top of an opening. This element enables drainage of potential rainwater and protects the facade system. The flashing must be secured with two rivets during installation.

Pre-install gasket into HF profiles

Self-adhesive tape 6x25xL (ID: 3017631) must be applied to the internal legs of the HF102/1 aluminium profile. Surfaces must be clean and dry. Use a roller or squeegee to press the tape firmly for optimal adhesion.

The gasket (ID: 30023441) must be manually applied to the edge of the HF140/1 aluminium prolongation profile.



panel	panel
panel	panel
panel	panel

Fig. 3.7: correct panel alignment

panel	X
panel	X
panel	X

Fig. 3.7.1: incorrect panel alignment

1. Mastic sealant
2. Steel plate position
3. Profile drip flashing

C

• C1 HORIZONTAL ORIENTATION

C1.4 FINALISING PANEL WALL WITH FLASHINGS AND FINISHING ELEMENTS

WALL 1 (COVER FLASHING & CORNER FLASHINGS)

Fill the gap with mineral wool

To complete the installation, any exposed wool surfaces must be appropriately protected against the weather. Insert soft mineral wool (class A1, density > 100 kg/m³) into the gap between panels to improve thermal and acoustic insulation. Protect the wool with vapour-permeable adhesive tape to prevent water ingress.


Check water tightness

Inspect all joints and sealing areas to ensure proper water tightness. Facade terminations need extra care.

Install flashings

Install flashings according to design details to protect joints and edges from water ingress and to complete the facade visually. Drawings of standard flashings are presented in a separate catalogue.

For HF140 profiles, follow the project-specific fixing details.



C


WALL 2 (HF PROFILE & CORNER ELEMENTS)

HF profiles prolongation

Check the location where HF profile prolongation will be applied. If prolongation is needed, the profile must be modified on-site before installation onto the facade. For detailed guidance, refer to Chapter C4.4.

Install HF profiles

For HF102 profiles, refer to the structural calculations to determine the required number of screws. If not specified, the profile must be fastened at intervals no greater than 1.00 m.



C

Installation sequences

• C2 VERTICAL ORIENTATION

C.2.1 PREPARATION FOR PANEL INSTALLATION

WALL 1 (COVER FLASHING & CORNER FLASHINGS)

Verify substructure placement

Confirm that the supporting structure is present in all necessary locations for panel installation. These include extensions, the bottom edge on the foundation beam, the top edge at the parapet, and around window openings.

Check structural flatness

Assess the flatness of the substructure according to the guidelines outlined in chapter B3.1. Any deviations may affect panel alignment and sealing.

Confirm structural width


Ensure the substructure is wide enough to support the panels securely.

Apply sealing tape

To ensure proper sealing and thermal performance, install sealing tape along the perimeter of the installation area.



installation gridline (theoretical axis lines)



Mark theoretical axes

Draw theoretical axis lines on the substructure to compare the actual situation with the design plans. This step is essential for accurate alignment and positioning during installation.

WALL 2 (HF PROFILE & CORNER ELEMENTS)

Corner verification

At building corners, measure dimensions in both directions to ensure that corner elements can be installed accurately and without misalignment.

Screw position check


Review the planned screw locations carefully. In specific details, the screw may align directly with the axis of the substructure, potentially colliding with the flange of an HEA profile. If such a conflict is identified, notify the project designer and agree on a suitable resolution.

! NOTES & WARNINGS

Use Trimoterm FTV installation guide as a general reference. Details may differ from project to project. Always follow project-specific execution details.

Use sealant material that complies with project design requirements for thermal insulation, tightness, and fire resistance.

For any uncertainties, contact Trimo technical support.



C

• C2 VERTICAL ORIENTATION

C.2 INSTALLATION OF THE FIRST COLUMN OF PANELS

WALL 1 (COVER FLASHING & CORNER FLASHINGS)

Install initial L-profile (longitudinal)

Position the L-profile along the designated line to define the starting edge of the panel installation.

Install drip flashing

Install the drip flashing (the flashing must include a vertical leg that inserts into the panel core).

All assembly works have to be done according to project design documentation.

Place the first panel


Cut out the mineral wool core so that the outer steel sheet of the panel acts as a drip edge for water running down the facade (see also image on page 51). Align the first panel precisely in its intended position. Avoid handling the panels in heavy wind.

Check vertical alignment

Before fastening, use a spirit level to verify that the panel is vertically aligned.

Fasten the panel

To ensure structural integrity, secure the panel using screws, as specified in the static calculation.



C

WALL 2 (HF PROFILE & CORNER ELEMENTS)

Corner support verification

Inspect the support conditions of corner elements to ensure they are not suspended without adequate bottom support.




Fig. 3.8: Each panel is clearly marked with individual installation reference (example on the right). With Trimoterm FTV panels the reference is indicated on the internal side of longitudinal panel joint.



C

• C2 VERTICAL ORIENTATION

C2.3 INSTALLATION OF REMAINING PANELS

WALL 1 (COVER FLASHING & CORNER FLASHINGS)

Apply mastic seal

Before placing the second panel next to the first, apply mastic sealant to ensure airtightness on the internal side of the panel.

Compress panels to seal groove/tongue joint

Compress the panels firmly to achieve a tight groove/tongue connection.

Check vertical alignment of panels

Always verify the vertical alignment of panels during installation. Horizontal and vertical lines must be properly aligned, with special attention to transitions and connections with adjacent facade sections.

Remove protective foil from installed panels


Remove the protective foil from all installed panels no later than the end of the working day.

Fasten the panel


To ensure structural integrity, secure the panel using screws, as specified in the static calculation.

Protect panels against water and moisture

The installer is responsible for keeping panels dry until installation is complete. Trapped moisture can cause internal corrosion. Avoid installation during rain, snow, or dense fog.



NEXT STEP




NEXT STEP

Fig. 3.9: correct panel alignment



Fig. 4.0: incorrect panel alignment



C

• C2 VERTICAL ORIENTATION

C2.4 FINALISING PANEL WALL WITH FLASHINGS AND FINISHING ELEMENTS

WALL 1 (COVER FLASHING & CORNER FLASHINGS)

Fill the gap with mineral wool

Insert soft mineral (class A1, density $> 100 \text{ kg/m}^3$) wool into the gap between corner panels to improve thermal and acoustic insulation. Also fill other gaps with mineral wool as specified in the project details.

Check water tightness

Inspect all joints and sealing areas to ensure proper water tightness. Facade terminations need extra care.

Install flashings

Once the assembly of all sides of the building's walls has been completed, work continues with the installation of all flashings. Install the flashings according to the design details to protect joints and edges from water ingress and to visually complete the facade.

Drawings of standard flashings are presented in a separate catalogue.

1. Parapet cap
2. Fastening screw
3. Thermal insulation
4. HF102 fixing profile
5. Self adhesive sealing tape
6. Vapour permeable EPDM foil

P

Follow the project details and make sure there are no thermal bridges or water leaks.

Facade terminations are the most sensitive areas and need extra care.

All assembly works have to be done according to project design documentation.

T

Use vapour-permeable EPDM foil to ensure proper sealing and prevent water ingress.

Parapet cap flashings are fastened to the parapet cap support. Finish the parapet cap according to the project detail.

If you are working with thin sheet metal, use sheet metal techniques and shape the parapet accordingly. If you are using powder-coated elements, follow the manufacturer's instructions for fixing, extending, and sealing.

U

The protective film on the external side of flashing is removed right before the completion of works.

Finish the corners with flashing (the width depending on the panel thickness). A strip of sealing tape is applied in between flashings and panel facings to prevent water leakage.

S

Make sure the gap between panels is filled with mineral wool.

R

Q



The drip flashing mask is fastened to the support using blind rivets. All works have to be done according to project detail.

C

WALL 2 (HF PROFILE & CORNER ELEMENTS)

Consider HF102 profile prolongation

Check the location where HF profile prolongation will be applied. If prolongation is needed, the profile must be modified on-site before installation onto the facade. For detailed guidance, refer to Chapter C4.4..

Pre-install gasket into HF profiles

Self-adhesive tape 6x25xL (ID: 3017631) must be applied to the internal legs of the HF102/1 aluminium profile. Surfaces must be clean and dry. Use a roller or squeegee to press the tape firmly for optimal adhesion.

Fasten the panel

For HF102 profiles, follow the fastening instructions in the project documentation. If not defined, the profile must be fastened at intervals not exceeding 1.00 m.



U

Use vapour permeable EPDM foil to ensure proper sealing and prevent water ingress.

Parapet cap flashings are fastened to parapet cap support. Finish the parapet cap is done according to the project detail.

If you are working with thin sheet metal, use sheet metal techniques and shape the parapet accordingly. If you are using powder-coated elements, follow the manufacturer's instructions for fixing, extending, and sealing.

U



S

With application of HF102 aluminium profile consider the following:

- Verify the fastening points, as defined in the project documentation.
- Provide a detail of the joint where two HF profiles meet.
- Include a detail at the bottom or at locations where the HF profile is interrupted (e.g. at a window opening).

R

Fill the gap between panels with soft mineral wool.

Q

Check if profile drip flashing at the lower part of joint gap is correctly inserted so as to enable drainage of rainwater.

Q

The drip flashing mask is fastened to the support using blind rivets. All works have to be done according to project detail.

C3 Trimoterm FTV installation check list



CHECK-LIST				
Steps	Step description	Correct	Incorrect	Notes
1	Substructure meets tolerance requirements (horizontally, vertically, dimensions, plains).			
2	Facade element supports (vertical and horizontal) are installed according to details, dimensions, and plains.			
3	Panels protected from water during unloading and during installation.			
4	Sealing tapes installed onto the substructure according to the details.			
5	Protective foil fully removed from the panel's internal side before installation.			
6	Protective foil partially removed from panels' external side before installation, and fully removed every day after panel installation.			
7	Each panel positioned and levelled according to allowed tolerances.			
8	Each panel is through fastened with number and type of screws determined according to static calculation.			
9	HF102 panel fastened according to structural calculation. Panels need to be fastened through internal steel sheet as well.			
10	Drip element, aluminium profile prolongation, profile gasket - installed according to the details. (HF102, HF140).			
11	Flashings prolonged and joined with overlapping, and sealed. Water ingress into the panel is prevented.			

Tab. 1.4: Trimoterm FTV installation check list



D

Installation details

• D1 HORIZONTAL installation details

D1.1 Panel joint (fasteners and sealants)

This detail is provided as an illustrative example. All panels and related components must be installed in strict accordance with the project's installation drawings and the relevant sections of this guide. For the whole range of detail options, see system design details.

1. assembly step

Level and orient panels to allow water drainage.

Fasten each panel end with at least two fasteners.

Do not overtighten fasteners This prevents panel damage or deformation.

2. assembly step


Compress sealing tubes in the grooves of adjacent panels to approximately 80% of their original thickness.

Seal across the external and internal vertical flashing and fasten it to the outer sides of the panel tongue (male joint) to ensure vapour-tight joints.


3. assembly step

Fill the gap between panel ends with mineral wool and **seal** with vapour-permeable tape. Cover the joint with

vertical flashing and fasten it to the outer steel sheet of the panel using blind rivets [see chapter A4.1].



horizontal orientation



D

D1.2 Panel base

This detail is provided as an illustrative example. All panels and related components must be installed in strict accordance with the project's installation drawings and the relevant sections of this guide. For the whole range of detail options, see system design details:



Trimoterm FTV system design details

1. assembly step


Level and fasten the support profile (load bearer) to the concrete plinth at the height required according to the fastener manufacturer's instructions. Ensure the profile is leveled. The profile height defines the starting point of the installation. Apply butyl sealing tape to the external surface of the plinth.

2. assembly step


Before fastening the panel, fasten the U support profile for panel support. Fill the gap between the panel's longitudinal joint and the U profile with mineral wool. Flashing mask to the support using blind rivets. Fit the drip flashing with a 50 mm overlap.



horizontal orientation



Make small V cuts at the back of the flashing.



D1.3 Parapet wall

This detail is provided as an illustrative example. All panels and related components must be installed in strict accordance with the project's installation drawings and the relevant sections of this guide. For the whole range of detail options, see system design details:



Trimoterm FTV system design details

1. assembly step


Install EPDM sealing tape at the joint where the roof's thermal insulation connects to the panel. This ensures vapour barrier properties. Fasten each panel end with at least two fasteners.

2. assembly step



Install vapour-permeable EPDM foil over the panel, and optionally across the entire sub-structure, to prevent water ingress into the panel. Fasten the vapour barrier properties. Fasten each support profile through the panel's steel sheet into the sub-structure with screws spaced at approximately 1.0 m.

3. assembly step

Attach and fasten the parapet wall cap to the support profile with screws. Perform the connection of two parapet caps according to instructions (see chapter D3.3).



horizontal orientation



To ensure watertightness of the system, install EPDM sealing tape at the joint where the roof's thermal insulation connects to the panel.

D1.4 External corner

This detail is provided as an illustrative example. All panels and related components must be installed in strict accordance with the project's installation drawings and the relevant sections of this guide. For the whole range of detail options, see system design details:



Trimoterm FTV system design details

1. assembly step


Apply self-adhesive sealing tape between the structure and the inner steel sheet of the panel. Cut off the portion of the inner panel and fasten each panel end with at least two fasteners. Fill the gap between the corner so that the cut corresponds to the adjoining panel thickness. This eliminates the cold bridge.

2. assembly step



Remove protective foil from the inner side of the panel. Engage the corner and the outer steel sheet of the panel. Cut off the portion of the inner panel and fasten each panel end with at least two fasteners. Fill the gap between the corner so that the cut corresponds to the adjoining panel thickness. This eliminates the cold bridge.

3. assembly step

Apply sealing tape between the flashings and the outer steel sheet of the panel. Fasten the corner flashing to the outer steel sheet on the panel to be installed in at least two fasteners. Fill the gap between the corner panel ends with mineral wool. Perform proper extension of the flashing according to instructions (see chapter D3.1).



horizontal orientation



* Cut or fully remove the internal steel sheet of the standard panel at the building corner to eliminate thermal bridging.


D

Installation details

• D2 VERTICAL installation details

D2.1 Panel joint (fasteners and sealants)

This detail is provided as an illustrative example. All panels and related components must be installed in strict accordance with the project's installation drawings and the relevant sections of this guide. For the whole range of detail options, see system design details.




vertical orientation

1. assembly step

Bottom panels must be fully installed. Install the support profile that will later provide bearing for the upper panels. Before installation, prepare the upper panels by removing the mineral wool. Install the drip flashing to ensure proper drainage of water that may occur at the sheet and at the location where the joint of the upper panels. Mineral wool drip flashing will be inserted. The drip must also be installed to provide thermal insulation of the detail. A groove must be prepared in advance.

2. assembly step

3. assembly step




⚠ Remove the mineral wool part of the panel on site.

** Cut the notch on site.

D

D2.2 Panel base

This detail is provided as an illustrative example. All panels and related components must be installed in strict accordance with the project's installation drawings and the relevant sections of this guide. For the whole range of detail options, see system design details:



vertical orientation




Trimoterm FTV system design details

1. assembly step

Level the support profile (load bearer) and fasten it to the concrete plinth at the required height. This height defines the starting point of the installation. Apply sealing tape to the external surface of the plinth. Install the drip flashing to ensure proper drainage of any water at the joint between panels.

2. assembly step

Before fastening the panel, trim and remove the mineral wool core at the specified height. Insert the steel sheet and at the location where the fasteners together with the sealing tape between the flashing mask support with an overlap of at least 50 mm. and the panel's external steel sheet. Install and fasten the drip flashing mask support.



⚠ Remove the mineral wool part of the panel on site.

* Make small V cuts at the back of the flashing.

** Cut the notch on site.

D2.5 Internal corner


This detail is provided as an illustrative example. All panels and related components must be installed in strict accordance with the project's installation drawings and the relevant sections of this guide. For the whole range of detail options, see system design details:




Trimoterm FTV system design details

1. assembly step


Apply self-adhesive sealing tape between the structure and the inner steel sheet of the panels. Consider the installation sequence carefully, as incorrect sequencing may make this impossible to perform. Fasten the panel along its length with approximately one fastener per metre. Fill the gap between the panel's cut edge and the structure with mineral wool. When installing the second column of panels, take care not to damage the surface of adjacent panels with tools (see chapter D3.1).

2. assembly step**3. assembly step**

vertical orientation

**D2.6 Panel penetration (edge of panel example)**

This detail is provided as an illustrative example. All panels and related components must be installed in strict accordance with the project's installation drawings and the relevant sections of this guide. For the whole range of detail options, see system design details and Trimoterm fire application document.



vertical orientation

For penetrations through fire-rated partition walls, follow dedicated firestop installation instructions to ensure proper sealing and compliance with fire protection requirements.

1. assembly step

Locate the penetration on the wall panel and cut an opening (approx. 20 mm above and below opening). Install the pipe through the opening. Ensure that the walls, ensure the penetration is sealed [clearance].


Important: Every penetration weakens the panel. Before cutting, confirm that the opening is planned in the project. If not, consult the structural engineer to verify feasibility. Refer to chapter A6.2.

2. assembly step

Fill the internal joint with butyl sealant and fill the gap around the pipe with mineral wool. Apply self-adhesive sealing tape around the penetration.

3. assembly step

For partition walls, install decorative trims around the opening. For external walls, ensure the penetration is sealed through the opening. Ensure that the pipe does not rest against the panel. Fill watertight on the outside, typically using double steel sheets (upper and lower parts), sealing strips, and sealant. On the panel. Fill the gap around the pipe the interior side, apply a vapour barrier with color-matched sealant to the top of parts, sealing strips, and sealant. On not, consult the structural engineer to the panel. Fill the gap around the pipe the interior side, apply a vapour barrier verify feasibility. Refer to chapter A6.2. with mineral wool. Apply self-adhesive by taping all joints with aluminium tape. sealing tape around the penetration.



The configurations may not meet specific project requirements, so it's crucial for an expert to assess them against the actual criteria.

D3.3 Parapet cap extension and fitting

This detail is provided as an illustrative example.





Fig. 4.3: Parapet cap cross-section

1. assembly step

Join the parapet cap

Snap the parapet cap onto the metal sub-cap. Then fasten the parapet cap with screws as specified in the detail. Take care not to damage the waterproofing layers below (e.g., EPDM membrane).



1. Parapet flashing cap 1
2. Parapet flashing cap 2
3. Fastening screw
4. Vertical corner flashing

2. assembly step

Join the parapet cap

Execute the joint using a sheet-metal connection. Fasten the parapet cap with screws as specified in the detail.



3. assembly step

Join the parapet cap on edge

Apply the standing seam principle to the parapet edge. This ensures continuity of the parapet cap and provides a uniform appearance whereby all joints look consistent.



D3.4 Fitting of aluminium HF102 fixing profile


HF102 aluminium profiles serve not only a decorative and load bearing purpose but also provide sealing against water ingress. It is therefore essential to execute the drip edge detail and the profile extension detail correctly, in accordance with the instructions below. During installation, ensure that thermal expansion of the material is accommodated.

1. step

Cut the base of the HF102 aluminium profile on site. Prior to installation, apply pre-compressed sealing tape to the inner side of the aluminium profile.

2. step

Prior to installation, apply pre-compressed sealing tape to the inner side of the aluminium profile.



1. Fixing profile HF102
2. Decorative profile HF102/2
3. Profile drip flashing




Fig. 4.4: Profile drip flashing in position.




Fig. 4.5: Position of HF102 profile, and distance to Trimoterm panel.




Fig. 4.6: The base of the aluminium profile is diagonally cut on site by the installer.

Assembly of HF102 aluminium fixing profile

Prior to installation, EPDM 6x25 sealing tape should be applied to the HF102 aluminium fixing profile. The seal must be applied to the profile edge. The optimum processing temperature, both for the bonding elements and the ambient temperature, is between +15°C and +30°C (60°F and 85°F). To achieve an optimum bond strength, the bonding surfaces must be dry and free of dust, oil, and release agents.

The cutting of profiles to a required length should be carried out by a suitable portable saw with a function that accommodates variable cutting angles. The deviation allowed is ± 0.5 mm at a width of 102 mm.

1. assembly step

Apply the mastic seal in two longitudinal and transversal strips on the extension sealing tape on the internal side of the flashing. Install the extension flashing on the aluminium profile and fasten it with the EPDM 6x25xL self-adhesive sealing tape must be done at an angle of 45°.



**2. assembly step**

Fig. 4.7: Position of sealing tape on the HF102 aluminium profile.

1. Fixing profile HF102
2. 6x25xL self-adhesive sealing tape
3. Extension flashing
4. Rivet 4x10
5. Mastic sealant
6. Decorative profile HF102/2



The thermal dilatation gap on the HF102 profile extension must be min. 1 mm/1 m of profile +2 mm.


The HF102 fixing profile has the function of an edge fixing, but only for wind load. In order to transfer the load of the panel's weight, the back sheet metal of the panel must also be fastened.

D3.5 Fitting of aluminium HF140 extension profile

HF140 aluminium profiles serve not only a decorative purpose but also provide sealing against water ingress. It is therefore essential to execute the drip edge detail and the profile extension detail correctly, in accordance with the instructions below. During installation, ensure that thermal expansion of the material is accommodated.

1. step

Cut the base of the HF140 aluminium profile on site. Prior to installation apply pre-compressed sealing tape to the inner side of the aluminium profile.



1. Extension profile HF140
2. Decorative profile HF140/2
3. Profile drip flashing
4. Pre-compressed sealing tape




Fig. 4.8: Profile drip flashing in position.





Fig. 4.9: The base of the aluminium profile is diagonally cut on site by the installer.

Assembly of HF140 aluminium extension profile


The sealing gasket is part of the HF140 aluminium extension profile. The seal must be applied to the profile edge. It enables rainwater to penetrate the facade system.

The cutting of profiles to the required length should be carried out using a suitable portable saw with a function that accommodates variable cutting angles. The deviation allowed is ± 0.5 mm at a width of 140 mm.

1. assembly step



2. assembly step



1. Extension profile HF140
2. Extension flashing
3. Rivet 4x10
4. Mastic sealant
5. Self adhesive pre-compressed sealing tape
6. Decorative profile HF140/2




Fig. 5.0: Position of sealing tape on the HF140 aluminium profile

HF102 fixing profile assembly




Fig. 5.1 PROFILE BASE PROFILE EXTENSION

HF140 extension profile assembly




Fig. 5.2 PROFILE BASE PROFILE EXTENSION

E

Life-cycle management

E1 Replacement of damaged panels

Trimoterm facade panels can be replaced individually thanks to their modular and reversible design. Replacement of panels requires re-application of sealant prior to re-installing.


E1.1 Replacement principles

Instructions 1

This document explains the disassembly steps of a horizontally installed panel wall according to detail TE-H-01.01. Every panel is fastened with screws across the panel.

Instructions 2

This document explains the disassembly steps of a vertically installed panel wall according to detail TE-H-01.02. Every panel is fastened with screws across the panel.



Instructions for replacing of horizontal Trimoterm FTV panel

Instructions for replacing of vertical Trimoterm FTV panel

E

E2 Panel life-cycle assessment

This product is part of a wider material cycle in which resources move through extraction, manufacturing, installation, use, and end-of-life processes. This diagram presents the full life-cycle structure, from the product stage (A1–A3) through end-of-life (C1–C4) and the potential for reuse and recycling (D). A5 covers impacts linked to installation on the construction site, including handling, cutting, fastening, and the treatment of packaging and installation waste. Module C1 marks the first step of the end-of-life stage and includes the physical removal of the product from the building. Together, these interconnected stages define the product's overall life-cycle profile.




Fig. 5.3

E

E3 End of panel life-cycle

Panel waste can take various forms, including offcuts from panel cutting, leftover materials, damaged panels, or debris from building construction and demolition. These panel remnants should be disassembled into their individual layers, and the constituent materials should be separated accordingly.

For more information on the end-of-life treatment of Trimo's product waste and packaging materials, see:



Treatment of Trimo's products waste and packing materials document



INSTRUCTIONS FOR THE TREATMENT OF TRIMO'S PRODUCTS
WASTE AND PACKAGING MATERIALS

F

Related documents

F1 Related Trimoterm documents

This chapter contains all the relevant technical documents for additional information on Trimoterm panels. These documents include structural design data, technical specifications, guidelines, and other resources essential for a comprehensive understanding of the subject. For further information about the panels visit:



www.trimo-group.com/en/downloads/technical-documents

Insulated facade system - Trimoterm FTV	Fire-resistant internal wall system - Trimoterm FTV	Backing wall - insulated facade system - Trimoterm FTV	Foogiene - food and hygiene internal wall system - Trimoterm FTV	Flat roof system - Trimoterm FTV	Internal wall system - Trimoterm FTV
Trimoterm technical specifications	Trimoterm structural design data	Trimoterm flashing catalogue	Trimoterm accessories catalogue	Instructions for use / gripper for Trimoterm panels	Packaging, transport and storage for Trimoterm products
Trimoterm FTV product book	Trimoterm FTV book	Treatment of Trimo product waste and packing materials	Trimodesign YouTube channel		

Notes

HEADQUARTERS

TRIMO D.O.O.

PRIJATELJEVA CESTA 12,
8210 TREBNJE, SLOVENIA

T: +386 (0)7 34 60 200

F: +386 (0)7 34 60 127

TRIMO@TRIMO-GROUP.COM

WWW.TRIMO-GROUP.COM

GLOBAL PRESENCE



www.trimo-group.com/en/company/about-trimo/global-presence

Trim Group holds full copyrights on the information and details provided in this document, therefore any unauthorised reproduction and distribution is strictly prohibited. Professional Care has been taken to ensure that the information/details are accurate, correct, complete and not misleading. However, Trim, including its subsidiaries, does not accept responsibility or liability for errors or information, which is found to be misleading. Information/details in this document are for general purposes only. It is the user's responsibility to check compliance with local laws. Any deviations in details and project solutions are the user's responsibility. Under no circumstances, will we be liable for any loss or damage including without limitation, indirect or consequential loss or damage, or any loss or damage whatsoever

arising from lost profits as a result of or in connection with the use of this document. All information issued by Trim Group is subject to continuous development and information/details contained in this document were current on the date of issue. It is the user's responsibility to obtain the most up-to-date information from Trim when information/details are used for a project. The latest version of the document is available at www.trimo-group.com. The latest version of the published document in English prevails over other translated documents.

For information about the delivery of panels see Trim's General conditions (<https://trimo-group.com/en/trimo/general-conditions-of-sale>).